

**Tableau de rechargement
35 Remington**

PROJECTILE BULLET			ETUI CASE	AMORCAGE PRIMER	POUDRE/POWDER VECTAN			VITESSE 2,5 ^m VELOCITY		PRESSION PRESSURE		NORMES CIP	
TYPE	POIDS/weight				TYPE	CHARGE		m/s	f/s	bars	psi	LONGUEUR Maxi Etui en mm	PRESSION Crusher Maxi en bars
	Grammes	grains				Grammes	grains						
SPEER F.N n° 2435	11.66	180	Remington	Rem. 91/2 LR	Tu2000	1.9	29.0	625.0	2051.0	1700.0	24650.0	48.77	2450
SPEER F.N n° 2435	11.66	180	Remington	Rem. 91/2 LR	Tu3000	2.3	35.0	630.0	2067.0	1750.0	25375.0	48.77	2450
SIERRA H.P n° 2800	12.96	200	Remington	Rem. 91/2 LR	Tu3000	2.45	38.0	645.0	2116.0	2000.0	29000.0	48.77	2450
SIERRA H.P n° 2800	12.96	200	Winchester RWS	CCI 200	SP10	2.35	36.0	670.0	2198.0	1900.0	27550.0	48.77	2450
SIERRA H.P n° 2800	12.96	200	Winchester RWS	CCI 200	SP9	2.55	39.0	680.0	2231.0	1900.0	27550.0	48.77	2450
RCBS coulé n° 35-200-FN	12.96	200	Remington	Rem. 91/2 LR	Tu2000	1.5	23.0	520.0	1706.0	1400.0	20300.0	48.77	2450