

**Tableau de rechargement  
458 Winchester Magnum (11,6 x 63)**

PROJECTILE BULLET			ETUI CASE	AMORCAGE PRIMER	POUDRE/POWDER VECTAN			VITESSE 2,5 m VELOCITY		PRESSION PRESSURE		NORMES CIP	
TYPE	POIDS/weight				TYPE	CHARGE		m/s	f/s	bars	psi	LONGUEUR	PRESSION Crusher
	Grammes	grains				Grammes	grains					Maxi Etui en mm	Maxi en bars
Hornady RN n° 4502	22.68	350	Remington	Rem. 91/2 Mag	Tu2000	4.15	64.0	700.0	2297.0	2300.0	33350.0	63.5	3700
SPEER SP n° 2479	25.92	400	Remington	Rem. 91/2 Mag	Tu2000	4.15	64.0	680.0	2231.0	3050.0	44225.0	63.5	3700
SPEER SP n° 2479	25.92	400	Remington	Rem. 91/2 Mag	Tu3000	4.3	66.0	645.0	2116.0	2250.0	32625.0	63.5	3700
SPEER FN n° 2479	25.92	400	Remington	CCI 200	SP9	4.8	74.0	680.0	2231.0	2800.0	40600.0	63.5	3700
SPEER FN n° 2479	25.92	400	Remington	CCI 200	SP10	4.6	71.0	690.0	2264.0	2600.0	37700.0	63.5	3700
Hornady SP n° 4507	32.4	500	Remington	Rem. 91/2 Mag	Tu2000	4.0	62.0	620.0	2034.0	3150.0	45675.0	63.5	3700
Hornady SP n° 4507	32.4	500	Remington	Rem. 91/2 Mag	Tu5000	4.5	69.0	590.0	1936.0	2400.0	34800.0	63.5	3700
Hornady 4507	32.4	500	Remington	CCI 200	SP9	4.6	71.0	630.0	2067.0	3100.0	44900.0	63.5	3700
Hornady 4507	32.4	500	Remington	CCI 200	SP10	4.45	68.0	650.0	2133.0	3400.0	49300.0	63.5	3700
RCBS coulé 45-405	26.24	405	Remington	CCI 200	Ba6	1.5	23.0	340.0	1116.0	950.0	13775.0	63.5	3700