

**Tableau de rechargement  
7 mm - 08 Remington**

PROJECTILE BULLET			ETUI CASE	AMORCAGE PRIMER	POUDRE/POWDER VECTAN			VITESSE 2,5 <sup>m</sup> VELOCITY		PRESSION PRESSURE		NORMES CIP	
TYPE	POIDS/weight				TYPE	CHARGE		m/s	f/s	bars	psi	LONGUEUR Maxi Etui en mm	PRESSION Crusher Maxi en bars
	Grammes	grains				Grammes	grains						
SPEER n° 1617	7.45	115	Remington	CCI 200	SP7	2.75	42.0	870.0	2854.0	2400.0	34800.0	51.69	3585
SPEER HP-BT n° 1631	9.4	145	Remington	Winch. LR	Tu3000	2.6	40.0	855.0	2805.0	3550.0	51475.0	51.69	3585
SPEER HP-BT n° 1631	9.4	145	Remington	Winch. LR	Tu5000	2.76	43.0	855.0	2805.0	3300.0	47850.0	51.69	3585
SPEER n° 1628	9.4	145	Remington	CCI 200	SP7	2.65	41.0	820.0	2690.0	3200.0	46400.0	51.69	3585
GIAT HP	9.4	145	GIAT	Federal 210	Tu5000	2.76	43.0	870.0	2854.0	3450.0	50025.0	51.69	3585
SIERRA HP-BT n° 1915	9.72	150	Remington	Winch. LR	Tu3000	2.55	39.0	830.0	2723.0	3350.0	48575.0	51.69	3585
SIERRA HP-BT n° 1915	9.72	150	Remington	Winch. LR	Tu5000	2.7	42.0	835.0	2740.0	3350.0	48575.0	51.69	3585
HORNADY HP-BT n° 2840	10.5	162	Remington	Winch. LR	Tu3000	2.45	38.0	800.0	2625.0	3450.0	50025.0	51.69	3585
HORNADY HP-BT n° 2840	10.5	162	Remington	Winch. LR	Tu5000	2.63	41.0	805.0	2641.0	3400.0	49300.0	51.69	3585