

Tableau de rechargement 357 Magnum

| PROJECTILE BULLET | | | ETUI CASE | AMORCAGE PRIMER | POUDRE/POWDER VECTAN | | | VITESSE 2,5 m VELOCITY | | PRESSION PRESSURE | | NORMES CIP | |
|-------------------|--------------|--------|--------------|-----------------|----------------------|---------|--------|------------------------|--------|-------------------|-------|--------------------------------|--|
| TYPE | POIDS/weight | | | | TYPE | CHARGE | | m/s | f/s | bars | psi | LONGUEUR Maxi Etui en mm | PRESSION Crusher Maxi en bars |
| | Grammes | grains | | | | Grammes | grains | | | | | | |
| SPEER JHP no 4007 | 7.13 | 110.0 | Norma | CCI 500 | Ba9 | 0.68 | 10.5 | 505.0 | 1656.0 | 2900 | 42000 | 32.77 | 3200 |
| SPEER JHP no 4007 | 7.13 | 110.0 | Norma | CCI 500 | SP3 | 1.25 | 19.2 | 450.0 | 1476.0 | 1700 | 24600 | 32.77 | 3200 |
| SPEER JHP no 4013 | 8.10 | 125.0 | Norma | CCI 500 | Ba9 | 0.65 | 10.0 | 460.0 | 1509.0 | 2700 | 39100 | 32.77 | 3200 |
| SPEER JHP no 4013 | 8.10 | 125.0 | Norma | CCI 500 | SP3 | 1.25 | 19.2 | 460.0 | 1509.0 | 2000 | 29000 | 32.77 | 3200 |
| SPEER JHP no 4013 | 8.10 | 125.0 | Norma | CCI 500 | A1 | 0.56 | 8.6 | 430.0 | 1410.0 | 2500 | 36200 | 32.77 | 3200 |
| SPEER JHP no 4013 | 9.07 | 140.0 | Hirtenberger | CCI 500 | Ba9 | 0.60 | 9.2 | 420.0 | 1378.0 | 2800 | 40600 | 32.77 | 3200 |
| SPEER JHP no 4013 | 9.07 | 140.0 | Hirtenberger | CCI 500 | SP3 | 1.15 | 17.7 | 430.0 | 1410.0 | 2000 | 29000 | 32.77 | 3200 |
| SFM BlindÉ | 9.60 | 148.0 | SFM | RWS 4031 | SP3 | 1.26 | 19.4 | 470.0 | 1542.0 | 2100 | 30450 | 32.77 | 3200 |
| SIERRA no 8360 | 10.20 | 158.0 | Norma | CCI 500 | SP3 | 1.05 | 16.2 | 435.0 | 1427.0 | 1850 | 26800 | 32.77 | 3200 |
| CoulÉ RCBS | 10.45 | 161.0 | Norma | CCI 500 | SP3 | 1.20 | 18.5 | 420.0 | 1378.0 | 2500 | 36200 | 32.77 | 3200 |

| | | | | | | | | | | | | | |
|------------------------|-------|-------|---------|------------------|--------------|------|------|-------|--------|------|-------|-------|------|
| 38-162 avec GC | | | | | | | | | | | | | |
| SFM- SILH- MÉtal | 11.66 | 180.0 | SFM | NCS 1113 | SP3 | 1.05 | 16.2 | 385.0 | 1263.0 | 1800 | 26100 | 32.77 | 3200 |
| SPEER SILH 4229 | 11.66 | 180.0 | Norma | CCI 500 | SP3 | 1.03 | 15.8 | 430.0 | 1410.0 | 2400 | 34800 | 32.77 | 3200 |
| H & N SWC | 10.23 | 158.0 | Norma | CCI 500 | NEW - SP2 | 0.85 | 13.1 | 484.0 | 1588.0 | 2450 | 35525 | 32.77 | 3200 |
| SPEER SWC | 11.66 | 180.0 | Norma | CCI 500 | NEW - SP2 | 0.75 | 11.6 | 441.0 | 1447.0 | 2060 | 29870 | 32.77 | 3200 |
| Hornady RN 3515 | 12.96 | 200.0 | FÉdÉral | FÉdÉral 205 M | NEW - SP2 | 0.75 | 11.6 | 398.0 | 1306.0 | 2225 | 32260 | 32.77 | 3200 |