

**Tableau de rechargement
38 Special Wad Cutter**

PROJECTILE BULLET			ETUI CASE	AMORCAGE PRIMER	POUDRE/POWDER VECTAN			VITESSE 2,5 m VELOCITY		PRESSION PRESSURE		NORMES CIP	
TYPE	POIDS/weight				TYPE	CHARGE		m/s	f/s	bars	psi	LONGUEUR Maxi Etui en mm	PRESSION Crusher Maxi en bars
	Grammes	grains				Grammes	grains						
Lyman coulÈ 35-84-95	9.40	145.0	Remington	RWS 4031	Ba10	0.15	2.3	220.0	721.0	950	13800	29.34	1300
HN PlastifiÈ BC dia. 357	9.40	145.0	Remington	RWS 4031	Ba10	0.15	2.3	220.0	721.0	900	13000	29.34	1300
HN PlastifiÈ BP dia. 355	9.52	147.0	Remington	RWS 4031	Ba10	0.15	2.3	210.0	689.0	750	10900	29.34	1300
Speer Bevel Base no 4605	9.60	148.0	Remington	RWS 4031	Ba10	0.16	2.5	225.0	738.0	860	12500	29.34	1300
Norma WC-BC	9.60	148.0	Norma	CCI 500	Ba10	0.15	2.3	220.0	721.0	1050	15200	29.34	1300
Norma WC-BC	9.60	148.0	Norma	CCI 500	AS	0.16	2.5	220.0	721.0	900	13000	29.34	1300
Lynx coulÈ HR - P 916	10.10	156.0	Remington	RWS 4031	Ba10	0.15	2.3	215.0	705.0	960	13900	29.34	1300