

Tableau de rechargement 44 Remington Magnum

PROJECTILE BULLET			ETUI CASE	AMORCAGE PRIMER	POUDRE/POWDER VECTAN			VITESSE 2,5 m VELOCITY		PRESSION PRESSURE		NORMES CIP	
TYPE	POIDS/weight				TYPE	CHARGE		m/s	f/s	bars	psi	LONGUEUR	PRESSION Crusher
	Grammes	grains				Grammes	grains					Maxi Etui en mm	Maxi en bars
SPEER J-MAG HP no 4425	12.96	200.0	Federal	CCI 300	Ba9	0.80	12.3	420.0	1378.0	2400	34800	32.64	2800
SPEER J-MAG HP no 4425	12.96	200.0	Federal	CCI 300	Ba6	1.60	24.6	440.0	1443.0	2500	36200	32.64	2800
SPEER J-MAG HP no 4425	12.96	200.0	Federal	CCI 300	SP3	1.70	26.2	445.0	1460.0	2150	31200	32.64	2800
SPEER JHP no 4435	14.58	225.0	Federal	CCI 300	Ba9	0.67	10.3	370.0	1213.0	2300	33300	32.64	2800
SPEER JHP HP no 4425	14.58	225.0	Federal	CCI 300	SP3	1.65	25.4	430.0	1410.0	2600	37700	32.64	2800
SPEER J-MAG HP	15.55	240.0	Winchester	CCI 300	SP3	1.60	24.6	415.0	1361.0	2400	34800	32.64	2800
Lyman Coulé 429421	16.50	255.0	Remington	CCI 300	Ba9	0.72	11.0	370.0	1213.0	2200	31900	32.64	2800
Lyman Coulé 429421	16.50	255.0	Remington	CCI 300	SP3	1.60	24.6	430.0	1410.0	2450	35500	32.64	2800

Lyman coulé GC no 429244	17.38	268.0	Remington	CCI 350	SP3	1.50	23.0	405.0	1328.0	2600	37700	32.64	28000
Speer HP	12.96	200.0	R. P	CCI 300	NEW - SP2	1.30	20.0	516.0	1593.0	2400	34800	32.64	2800
Speer JHP	14.58	225.0	RP	CCI 300	NEW - SP2	1.20	18.5	481.0	1578.0	2475	35890	32.64	2800
Hornady	15.55	240.0	WWSuper	CCI 350	NEW - SP2	1.22	18.8	477.0	1565.0	2600	37700	32.64	2800
Speer	15.55	240.0	RP	CCI 300	NEW - SP2	1.16	17.9	461.0	1512.0	2340	33900	32.64	2800